




A Furukawa Company

UltraSil® 330 μm Optical Fiber

P/N: BF04746-02



Overview

The high-numerical aperture and low-OH content of multimode step-index UltraSil Optical Fibers provide a wide window of operability to the end-user. Low OH concentration is especially effective for using these fibers in near-IR spectroscopy applications.

For laser delivery, the HCS® fluoroacrylate coating preserves cladding modes through bends and distributes lost power over a greater area—lowering the probability of “hot spots.”

For high-temperature performance, we recommend PYROCOAT® polyimide coating. This coating strips cladding modes for enhanced performance in sensing and spectroscopy applications.

Typical Applications

Cascaded Laser Power Delivery
FTIR and Raman Spectroscopy
High-Power Laser Delivery
Medical Applications Near -
IR (up to 2100 μm) Laser Power
Delivery



A Furukawa Company

UltraSil® 330 µm Optical Fiber

P/N: BF04746-02

Product Specifications	
Product Description	330 0.29 NA Low OH
Physical Characteristics	
Core Diameter	330 ± 10 µm
Cladding Diameter	400 ± 8 µm
Buffer Diameter	730 ± 30 µm
Core/Clad Offset	≤ 8 µm
Crimp & Cleave Compatible	No
Buffer Material	ETFE
Coating Material	HCS® Fluoroacrylate
Optical Characteristics	
Type	Multimode Step-Index
Numerical Aperture	0.29
Attenuation @ 850 nm	≤ 12 dB/km
Water Content	Low OH
Mechanical and Environmental	
Operating Temperature	-65 to +125 °C
Short-Term Bend Radius	≥ 30 mm
Long-Term Bend Radius	≥ 49 mm
Proof Test Level	≥ 100 kpsi (0.689 GPa)
Order by Part Number	BF04746-02
Product Description Code	HCE-HB330T
OPTIONS: Buffer Color, Buffer Diameter, Buffer Material, Cabling, Connectorization, Core Diameter, Metalization, Numerical Aperture, Proof Test	

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2019 OFS Fitel, LLC.
All rights reserved, printed in USA.

OFS Marketing Communications
Date: 11/19

HCS, PYROCOAT and UltraSil are registered trademarks of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.