



A Furukawa Company

F07 Crimp & Cleave Termination Kit

P/N: DT03732-37



Overview

OFS' F07-system crimp and cleave termination kit is designed for use with F07 connectors and our 200 μm zipcord and duplex 200 μm HCS[®] fiber-based cables.

Product Specifications	
Product Description	F07 Crimp & Cleave Termination Kit
Compatibility	
For Use with Connector Types	BP05974 , F07 Connectors for 200/230 µm HCS®
Compatible Insertion Loss Test Kit	P10188-07 , F07 Insertion Loss Test Kit P10188-08 , Multi-Set (4-Types: V-Pin, ST, SMA, and F07) Insertion Loss Test Kit
Connectors	
Connector Type	F07
Fiber Size	200 µm
Fiber Type	Standard
F07 Mating Adapter	AP02719
Connector Performance Data	
Overall Connector Dimension	1.375 in. (34.9 mm)
Insertion Loss	Maximum: 2.0 dB Typical: 1.5 dB
Kit Parts (Also Sold Separately)	
Diamond Cleave Tool	DT03732-02 (Green Spring)
Fiber Stripper	CP01229-20 (White Blade Insert)
Cable Stripper	AP01224
Crimp Tool	BT03865-05 (Blue Handles)
Scissors (Will Cut Through Aramid Yarn)	AP01225
Accessories	
Cleave Tool Cleaning Kit	P16247
General Properties	
Case Dimensions (H x W x D)	2.75 x 13.5 x 8.25 in.
Order by Part Number	DT03732-37

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2020 OFS Fitel, LLC.
All rights reserved, printed in USA.

OFS Marketing Communications
Date: 01/20

HCS and GiHCS are registered trademarks of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.